



MMA stick electrode welding machine in direct (DC) and alternating current (AC). Stepless regulation of welding current. With thermostatic protection. Use with a wide range of electrodes: rutile, basic, stainless steel and cast iron.



PROFESSIONAL



<p>COMPLIANCE WITH NEW CE MARKING</p>	<p>DUAL VOLTAGE POWER SUPPLY</p>	<p>STEPLESS CURRENT ADJUSTMENT</p>	<p>WITH FAN</p>	<p>OUTPUT AC/DC - ALL ELECTRODES</p> <p>AC/DC RUTILE BASIC INOX</p>
---------------------------------------	----------------------------------	------------------------------------	-----------------	-------------------------------------------------------------------------------------------------------------

Norms:		LVD: EN 60974-1		EMC: EN 60974-10					
CODE	V _{ph} V50/60Hz	V _{ph} V50/60Hz	A _{MIN} A _{MAX} A	A _{MIN} A _{MAX} A	A _{MAX} 40°C A EN60974-1	A _{MAX} 40°C A EN60974-1	A _{60%} 40°C A EN60974-1	A _{60%} 40°C A EN60974-1	V _o V
814097	230 1 ph	400 2 ph	45 230 AC	25 160 DC	220 10 % AC	150 15% DC	90 AC	80 DC	55 AC
V _o V	P _{60%} kW	cosφ	Ø _{MIN} Ø _{MAX} E AC mm	Ø _{MIN} Ø _{MAX} E DC mm	IP	W _L H L cm(L,W,H)	kg	BAR CODE	pz/pallet
67 DC	3,3 7,2	0,5	1,6 5	1,6 4	IP22	75 36 49	40	8004897553 26 9	12