



MMA stick electrode welding machine in alternating current (AC). Stepless regulation of welding current. With thermostatic protection. Electrodes: rutile.



PROFESSIONAL



<p>COMPLIANCE WITH NEW CE MARKING</p>	<p>DUAL VOLTAGE POWER SUPPLY</p>	<p>SINGLE PHASE, CHEAP, POWERFUL</p> <p>POWER SINGLE PHASE</p>	<p>STEPLESS CURRENT ADJUSTMENT</p>	<p>THERMAL SWITCH/FAN PROTECTION</p>
---------------------------------------	----------------------------------	--	------------------------------------	--------------------------------------

Norms: LVD: EN 60974-1 EMC: EN 60974-10

CODE	V _{ph} V50/60Hz	V _{ph} V50/60Hz	A _{MIN} A _{MAX} A	A _{MAX} 40°C A EN60974-1	A _{60%} 40°C A EN60974-1	V _o V	P _{60%} MAX kW	φ cosphi	∅ _{MIN} MAX E AC mm
817015	230 1 ph	400 2 ph	60 250 AC	200 10 % AC	80 AC	55 AC	2,5 8	0,55	2 5
IP	W _H L cm(L,W,H)	kg	BAR CODE	pz/pallet					
IP22	69 39 48	27	8004897847 87 0	12					