



MMA stick electrode welding machine in alternating current (AC). Stepless regulation of welding current. With thermostatic protection. The model has double secondary voltage for use also with basic and rutile electrodes.



**DUAL AC
2AC**

PROFESSIONAL



<p>COMPLIANCE WITH NEW CE MARKING</p>	<p>DUAL VOLTAGE POWER SUPPLY</p>	<p>SINGLE PHASE, CHEAP, POWERFUL</p> <p>POWER SINGLE PHASE</p>	<p>STEPLESS CURRENT ADJUSTMENT</p>	<p>DOUBLE OUTPUT VOLTAGE</p> <p>LOW RUTILE</p> <p>HIGH BASIC AC</p>
---------------------------------------	----------------------------------	---	------------------------------------	---

Norms: LVD: EN 60974-1 EMC: EN 60974-10

CODE	V _{ph} V50/60Hz	V _{ph} V50/60Hz	A _{MIN MAX} A	A _{MAX} 40°C A EN60974-1	A _{60%} 40°C A EN60974-1	V _o V	P _{60% MAX} kW	φ cosphi	∅ _{MIN MAX} E AC mm
817018	230 1 ph	400 2 ph	40 400 AC	350 35 % AC	265 AC	52 71 AC	11 15	0,7	1,6 6
IP	W _H cm(L,W,H)	kg	BAR CODE	pz/pallet	pz/pallet - B				
IP22	95 49 68	81	8004897850 92 4	6	3				