



MMA, rectified, electrode welding machine in direct current (DC). Stepless regulation of welding current. Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron and aluminium.



PROFESSIONAL



<p>COMPLIANCE WITH NEW CE MARKING</p>	<p>THREE PHASE 3PH</p>	<p>HIGH DUTY CYCLE (HD)</p>	<p>OUTPUT DC - ALL ELECTRODES</p>	<p>BUILT TOUGH</p>
			<p>DC RUTILE BASIC INOX ALUMINIUM</p>	

Norms:		LVD: EN 60974-1	LVD: EN 50445	EMC: EN 60974-10					
CODE	V <sub>ph</sub>	A <sub>MIN</sub> A <sub>MAX</sub>	A <sub>MAX</sub> 40°C	A <sub>60%</sub> 40°C	V <sub>o</sub>	P <sub>60%</sub> MAX	cosphi	Ø <sub>E</sub> MIN MAX DC	IP
819052	230 / 400 3 ph	60 360 DC	325 35 % DC	240 DC	65 DC	10 15 kW	0,6	2 6 mm	IP22
cm(L,W,H)	kg	BAR CODE	pz/pallet						
100 54 76	110,7	8004897778 60 0	3						