



MMA inverter, electrode welding machine in direct current (DC). Use with a wide range of electrodes:rutile, basic, stainless steel, cast iron, etc. Characteristics: compact and light * high welding current stability in spite of mains voltage fluctuations * arc force, hot start and anti-stick devices * thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections. Complete with MMA welding accessories and cardboard carry case.


CONSUMER


20°C	ELECTRODES IN 10 MIN		20" STOP
Ø (I)	1,6mm (40A)	2,0mm (55A)	2,5mm (80A)
10 MIN	10,3	5,2	3,9
% USE ^(*) _{20°C}	100%	62%	50%

COMPLIANCE WITH NEW CE MARKING 	SUPPLY WITH MOTOGENERATORS (VIN +/-15%) MOTOGENERATOR POWER - SOURCE	ARC FORCE, HOT START, ANTI-STICK DEVICES ARC FORCE HOT START ANTI STICK	LOW ENERGY CONSUMPTION ENERGY SAVING!	STEEL, STAINLESS STEEL, CAST IRON
---	--	---	---	--

Norms:	LVD: EN 60974-1	LVD: EN 50445	EMC: EN 60974-10						
CODE	V_{ph} V50/60Hz	A_{MIN MAX} A	%USE_{20°C} %	A_{MAX 40°C} A EN60974-1	V_o V	A_{MAX} A	P_{MAX} kW	P_{GEN} kW	A A
815855	230 1 ph	10 80 DC	45% 80A	80 5% DC	72 DC	15	2,3	3	10
η n%	φ cosphi	Ø_{E MAX DC} mm	IP	W_L cm(L,W,H)	kg kg	BAR CODE	pz/pallet		
70	0,6	1,6 2,5	IP21	37 37 15	3,55	8004897789 53 8	42		

(*)%USE:DATUM CREATED BY TELWIN, NOT INCLUDED IN THE EN 60974-1.