



MMA inverter, electrode welding machine in direct current (DC). Usable electrodes: rutile, basic, stainless steel, cast iron, etc. Characteristics: reduced weight and dimensions \* high welding current stability in spite of mains voltage fluctuations \* arc force, hot start and anti-stick devices \* thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator ( $\pm 15\%$ ) protections. Complete with MMA welding accessories and plastic carry case.


**CONSUMER**


20°C	ELECTRODES IN 10 MIN			20" STOP
Ø (I)	2,0mm (55A)	2,5mm (80A)	3,2mm (115A)	4,0mm (150A)
10 MIN	8,3	7,9	6,0	3,6
%USE <sup>(*)</sup> <sub>20°C</sub>	100%	100%	80%	60%

<b>COMPLIANCE WITH NEW CE MARKING</b> 	<b>SUPPLY WITH MOTOGENERATORS (VIN +/-15%)</b>  MOTOGENERATOR POWER - SOURCE	<b>ARC FORCE, HOT START, ANTI-STICK DEVICES</b>  ARC FORCE HOT START ANTI STICK	<b>LOW ENERGY CONSUMPTION</b>  ENERGY SAVING!	<b>STEEL, STAINLESS STEEL, CAST IRON</b> 
---	--	---	---	--

Norms:	LVD: EN 60974-1	LVD: EN 50445	EMC: EN 60974-10						
CODE	V <sub>ph</sub>	A <sub>MIN</sub> / A <sub>MAX</sub>	%USE <sub>20°C</sub>	A <sub>MAX</sub> <sub>40°C</sub>	V <sub>o</sub>	A <sub>MAX</sub>	P <sub>MAX</sub>	P <sub>GEN</sub>	A
η	cosφ	Ø <sub>E</sub> / Ø <sub>MAX DC</sub>	IP	W <sub>L</sub> / W <sub>H</sub> / W <sub>L</sub>	kg	BAR CODE	pz/pallet		
815857	230 1 ph	10 150 DC	60% 150A	140 7% DC	72 DC	31	4,1	6	16
82	0,6	1,6 4	IP21	38 42 17	5,5	8004897789 55 2	36		

(\*)%USE: DATUM CREATED BY TELWIN, NOT INCLUDED IN THE EN 60974-1.